

## POWDER COATED Metal Toilet Partitions

### M a i n t e n a n c e   P r o c e d u r e



**1 . 0 1**

#### **P o w d e r   C o a t e d   P a i n t e d   F i n i s h**

---

Maintenance of your toilet partitions should be a part of your regular building preventive maintenance procedure.

- 1** Tighten any screws that have become loose due to vibrational forces or attempted vandalism.
- 2** Check the top door pin to be sure it is flush with the top of the hinge.
- 3** Be sure the surfaces are dry after being cleaned and rinsed with clear water (when required).
- 4** Partitions exposed to severe humidity should be washed and dried frequently. If partitions are in a shower room, a coat of paste wax is recommended on painted surfaces.
- 5** Periodically, remove any dirt, grime or foreign matter with a soft cloth.
- 6** Where surfaces reveal spotting resulting from hand perspiration, soil, or grease, a thorough cleaning with warm water and a mild detergent (i.e. Ivory Soap), followed by rinsing, and removal of excess moisture, will renew the clean even surface, providing a pleasant sanitary appearance. (Use of cleaning agents containing abrasives such as household cleaning powder, steel wool, and harsh detergents or acids ARE NOT RECOMMENDED.
- 7** To maintain the brilliance of hardware, these components can be periodically improved by an application of non-abrasive cleaner with a damp cloth.
- 8** Where additional gloss and protection is desirable, light applications of commercial liquid or paste waxes are highly recommended.
- 9** If your partitions have a continuous hinge, regular application of an LPS II or an industrial type, non-drying lubricant is recommended.



**Hadrian Manufacturing Inc.,**

**Hadrian Inc.,**

**www.hadrian-inc.com**

965 Syscon Road, Burlington, ON, Canada, L7L 5S3

7420 Clover Avenue, Mentor, OH, U.S.A., 44060

• Tel: (905) 333-0300

• Tel: (440) 942-9118

• Fax: (905) 333-1841

• Fax: (440) 942-9618