


Inverter Generators

2000-Watt up to 7300-Watt – Gasoline

These inverters provide clean and quiet power for jobsites, workshops, recreation and power outages. They are equipped with carbon monoxide detection and auto shutdown.



GEN-8000-IMM1E



120V Duplex
All Models



NEMA L5-30R
120VAC
GEN-3500,
GEN-4000 &
GEN-8000 Models



NEMA L14-30R
120V/240V
GEN-8000 Model



Quiet Technology

**EQUIPPED WITH
CO DETECTOR**

Inverter Technology

- Reduced size, weight, noise and fuel consumption
- Produces commercial quality AC power for sensitive electronic equipment

Alternator

- Total harmonic distortion (THD) less than 3%
- Copper windings

Engine

- Low-oil shutdown
- Recoil start (GEN-4000 and GEN-8000 models also have electric start - sealed battery included)

Components

- Equipped with CO detector with automatic shutdown
- DC plug
- USB ports for electronics
- Idle control
- Gas ventilation cap (GEN-2000-IMM1)
- Battery charger (GEN-4000 and GEN-8000 models)
- Digital display for voltage, hertz, run hours and total hours (GEN-4000 and GEN-8000 models)
- Main circuit breaker
- USDA/USFS-approved spark arrestors

Frame

- Easy to remove access panels for spark plug, oil and air cleaner
- Handles and wheels (GEN-4000 and GEN-8000 models)
- Tool storage compartment (GEN-4000-IMM1E)
- Outlet covers

Limited Warranties

- 1 year alternator
- 3 year Mi-T-M engine

Certifications

- CSA Certified - Canada (GEN-2000 and GEN-3500 models)
- ETL Certified - Canada (GEN-2500, GEN-4000 and GEN-8000 models)



GEN-2000-IMM1



GEN-2500-IMM1



GEN-3500-IMM1



GEN-4000-IMM1E



GEN-8000-IMM1E

USAGE	RESIDENTIAL/ COMMERCIAL	RESIDENTIAL/ COMMERCIAL	RESIDENTIAL/ COMMERCIAL	RESIDENTIAL/ COMMERCIAL	RESIDENTIAL/ COMMERCIAL
MODEL NUMBER	GEN-2000-IMM1	GEN-2500-IMM1	GEN-3500-IMM1	GEN-4000-IMM1E	GEN-8000-IMM1E
MAX. AC OUTPUT	2000 watts	2500 watts	3500 watts	4000 watts	7300 watts
RATED AC OUTPUT	1600 watts	2300 watts	3200 watts	3500 watts	6800 watts
DISPLACEMENT/ENGINE	79cc Mi-T-M OHV	120cc Mi-T-M OHV	212cc Mi-T-M OHV	225cc Mi-T-M OHV	420cc Mi-T-M OHV
MAX. AMPS (120V)	16.7	20.8	29.2	33.3	60.8
CONT. AMPS (120V)	13.3	19.2	26.7	29.2	56.7
RECEPTACLES	(1) 120V, 20A GFCI duplex (1) 12V DC 8.3A	(1) 120V, 20A GFCI duplex (1) 12V DC 8.3A	(1) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 12V DC 8.3A	(1) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 12V DC 8.3A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 12V DC 8.3A
RATED SPEED	5000 RPM	4400 RPM	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	69,0	67,0	76,0	56,0	70,0
FUEL CAPACITY	1,0 gallon	1,0 gallon	1.8 gallons	2,1 gallons	5,5 gallons
RUN TIME (AT HALF LOAD)	6,0 hours	5,0 hours	8,0 hours	8,0 hours	9,0 hours
DIMENSIONS (LxWxH)	19,6x12,5x18,1in.	21,5x13,4x19,3in.	19,8x13,8x19,5in.	25,4x18,5x20,4in.	34,3x28,6x27,1in.
SHIP WT.	57 lb.	68 lb.	77 lb.	118 lb.	238 lb.
NET WT.	49 lb.	57 lb.	66 lb.	105 lb.	227 lb.

Inverter generator ratings represent no-load sound levels. Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	GEN-3500, GEN-4000 & GEN-8000 models
32-1289	Triple receptacle adapter	GEN-3500, GEN-4000 & GEN-8000 models
AW-5100-0001	Parallel port box – Connect two models for a maximum output of 3600-watts	GEN-2000-IMM1 & GEN-2500-IMM1
AW-5100-0002	Parallel port box – Connect two models for a maximum output of 6000-watts	GEN-3500-IMM1 & GEN-4000-IMM1E
AW-6000-1002	Equipment cover	GEN-8000-IMM1E