

F0760 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 201 gallons
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -20°C up to +55°C (with reduced specifications)
- Refrigeration system includes 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system
- NDH version available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). It maintains consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP
- AC/DC power supplies available as accessories

Available versions:

- ☐ NDN down to +32°F
- ☐ FDN down to -6°F
- ☐ NDH from +86°F to +32°F



easy cooling, smart moving

www.coldtainer.com

F0760
PRODUCT INFO

Model name	F0760/NDN	F0760/FDN
EE article nr.	816020/00	816020/01
Gross capacity (gal)	201	201
Temperature range (°F)*	down to +32°F	down to -6°F
ATP class	FRAX	FRCX
Voltage	12-24 Vdc	12 Vdc
Peak Amps (@12Vdc)	18A	25A
Fuse on DC cord	50A	50A
External dimensions (in)	32,3 x 56 x 62,2	32,3 x 56 x 62,2
Weight (lb)	347	364
PU insulation (in)	3,9	3,9
"K" insulation factor	0,35 W/m²K	0,35 W/m²K
Refrigerant gas (type)	R134a	R404A
Refrigerant gas (gr)	135	250
Cut-out / cut-in voltage	9,6 Vdc-10,9 Vdc	11 Vdc-12,3 Vdc
AC/DC power supply (opt)	560020/00	560021/00

F0760/NDH
816020/05
201
from +86°F to +32°F
BRBX**
12 Vdc
18A
50A
32,3 x 56 x 62,2
419
3,9
0,35 W/m²K
R134a
130
9,6 Vdc-10,9 Vdc
560020/00

*with ambient temperature +86°F

**available from Q3/2025

E57 10R-060148



032025 rev0 - Copyright©2025 Euroengel srl

