

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

1 Identification of the Substance/Mixture and of the Company/Undertaking

- **Product identifier**
- **Trade name:** Odyssey® 2 Toner for use in Lexmark® C Series - Yellow
- **Article number:** LCS-YOS2
- **Application of the substance / the mixture** Printing inks
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Static Control Components Inc.
P.O. Box 152
Sanford, North Carolina, 27331
info@scc-inc.com
- **Information department:** Product Safety Department
- **Emergency telephone number:**
During Normal Operating Hours: 919-774-3808
Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019

2 Hazards Identification

- **Classification of the substance or mixture**
Combustible Dust May form combustible dust concentrations in air.
- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
May form combustible dust concentrations in air.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
 Health = 1
Fire = 1
Reactivity = 0
- **HMIS-ratings (scale 0 - 4)**
 HEALTH 1 Health = 1
FIRE 1 Fire = 1
REACTIVITY 0 Reactivity = 0
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/Information on Ingredients

- **Chemical characterization:** Mixtures
- **Description:** Resin mixture

(Contd. on page 2)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 1)

· Dangerous components:		
13463-67-7	titanium dioxide (bound)	≤ 2.5%
· Non-hazardous components		
292629-36-8	Resin	50-100%
9002-88-4	Wax	10-25%
	Yellow Pigment	2.5-10%
68909-20-6	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	≤ 2.5%

4 First Aid Measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** No Information Available
- **Special hazards arising from the substance or mixture**
Like most finely divided organic powders, toner dust may form an explosive mixture in air.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Vacuum or sweep the material into a sealed container. If a vacuum is used it must be dust explosion-proof. Dispose of in compliance with national, state, regional or provincial regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**
 - No special measures required.
 - Store in cool, dry place in tightly closed receptacles.
 - Keep away from heat and direct sunlight.
 - No special precautions are necessary if used correctly.
 - Use only in well ventilated areas.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Store only in the original receptacle.
- **Information about storage in one common storage facility:**
 - Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Protect from humidity and water.
- **Specific end use(s)** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:**13463-67-7 titanium dioxide (bound)**

PEL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 10 mg/m ³ withdrawn from NIC

Additional Occupational Exposure Limit Values for possible hazards during processing:USA OSHA (TWA/PEL): 15 mg/m³ (Total Dust), 5 mg/m³ (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m³ (Inhalable Particulate), 3 mg/m³ (Respirable Particulate)Amorphous Silica: USA OSHA (TWA/PEL): 20mppcf 80 mg/m³, ACGIH (TWA/TLV): 10 mg/m³TRGS 900 (Luftgrenzwert): 10 mg/m³ (Einatembare partikel)). 3 mg/m³ (Alveolengängige fraktion)UK WEL: 10 mg/m³ (Respirable Dust) 5 mg/m³ (Inhalible Dust)

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 3)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale dust / smoke / mist.
- **Protection of hands:**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses

9 Physical and Chemical Properties

- | | |
|--|---|
| · Information on basic physical and chemical properties | |
| · General Information | |
| · Appearance: | |
| Form: | Powder |
| Color: | Yellow |
| · Odor: | Odorless |
| · Odor threshold: | Not determined. |
| · pH-value: | Not applicable. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | Undetermined. |
| · Flash point: | Not applicable. |
| · Flammability (solid, gaseous): | Not determined. |
| · Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard in its original state. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapor pressure: | Not applicable. |
| · Density at 20 °C (68 °F): | 1.03 g/cm ³ (8.595 lbs/gal)
SG: 1.3-1.8 |
| · Relative density | Not determined. |
| · Vapor density | Not applicable. |

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 4)

· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
· Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** Non reactive.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- **on the eye:** No toxic irritating effect, according to Directive 67/548/EEC or Directive 199/45/EC.
- **Sensitization:** No toxic sensitizing effects known, according to EU Directive 67/548/EEC or Directive 199/45/EC.
- **Other information (about experimental toxicology):**
Mutagenicity : Ames test Negative (According to the test result of similar composition.)
- **Additional toxicological information:**
The product is not subject to classification according to internally approved calculation methods for preparations:
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
9002-88-4	Wax	3
13463-67-7	titanium dioxide (bound)	2B

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 5)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological Information**· Toxicity****· Aquatic toxicity:** No further relevant information available.**· Persistence and degradability** No further relevant information available.**· Behavior in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment**· PBT:** Not applicable.**· vPvB:** Not applicable.**· Other adverse effects** No further relevant information available.**13 Disposal Considerations****· Waste treatment methods****· Recommendation:** Smaller quantities can be disposed of with household waste.**· Uncleaned packagings:****· Recommendation:** Disposal must be made according to official regulations.**14 Transport Information**

· UN-Number	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 6)

· Packing group	Not a regulated material under the United States DOT, IMDG, ADR, RID, or ICAO/IATA.
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

557-05-1 | zinc distearate, pure

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 | titanium dioxide (bound)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

557-05-1 | zinc distearate, pure

D, I, II

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7 | titanium dioxide (bound)

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 | titanium dioxide (bound)

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms** Void

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/02/2017

Reviewed on 08/08/2016

Trade name: Odyssey® 2 Toner for use in Lexmark® C Series - Yellow

(Contd. of page 7)

- **Signal word** Warning
- **Hazard statements**
May form combustible dust concentrations in air.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:**
During Normal Operating Hours: 919-774-3808
Emergency Telephone Number: 1-919-770-7984 or 1-919-770-6019
- **Date of preparation / last revision** 02/02/2017 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
- *** Data compared to the previous version altered.**
No changes to the Material Safety Data Sheet, all sections are current as the date of print seen above describes.