

APPLICATION:		PRODUCT NAME: POT FILLER HOSE STYLE SINGLE WALL MOUNT WITH VACUUM BREAKER	
JOB NAME:		☐ SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL: ☐ 2740	
VACUUM BREAKER WALL HOOK 2-3/8" [60.0mm] 5-1/4" [133.4mm] 2-1/2" [63.5mm] 4-3/8" (MAX) [111.1mm] 60" LENGTH HOSE ROUGH-IN: 1/2" NPT FEMALE Ø7/8" [22.2mm]		OPTIONS OR MODIFICATIONS: ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH ☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE LGTH ☐ IN-LINE DUAL CHECK VALVE ☐ PIPE HOOK ☐ NIPPLES ☐ ELBOWS ☐ VANDAL RESISTANT KIT ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE ☐ OTHER _____	
		FEATURES: CONTROL VALVE * SINGLE WALL MOUNT * STEM - RIGHT HAND * SWIVELING SEAT DISKS * HOT & COLD INDEX BUTTONS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS HOSE * 60" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * BRAIDED USDA APPROVED FOODGRADE INTERNAL HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS POT FILLER VALVE * NON SCRATCHING/ MARRING TUBE * 5.00 GPM AT 80 PSI * AERATED STREAM SWIVEL ELBOW * 360° TURNING RADIUS * ATMOSPHERIC VACUUM BREAKER SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC SHIPPING WEIGHT * 6.5 LBS	
FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com			