

30 Gallon Cast Iron - Oil Lubricated - Belt Drive Compressor

FEATURES AND BENEFITS

- Cast iron, V-twin cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Thermally stable cast iron cylinder body
 - Aluminum head and machined cast iron valve plate
 - Automotive style ball bearings
 - Durable stainless steel reed valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 10" cast iron balanced flywheel
- Heavy duty induction motor for maximum performance and efficiency
- 30 gallon ASME* portable tank equipped with pneumatic tires for maximum portability
- Dual voltage motor is wired for standard 120 volt outlet, and may also be converted for 240 volt application
- Fully assembled and equipped with quick-set regulator, tank and tool pressure gauges, quick connect air outlet and on/off switch for ease of use
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	30 Gallon ASME*
Maximum Pressure:	135 PSI
CFM @ 40 PSI:	6.2
CFM @ 90 PSI:	5.3
Voltage:	120/240 Volt
Running HP:	1.6
Certifications:	UL & CSA
Warranty:	2 Year Pump 1 Year All Other Parts



Dimensions: 25" x 24.5" x 49" • Weight: 167 lbs. • UPC: 8 46212 00620 7 • Pallet Qty: 4 • Truckload Qty: 192 (53' trailer)

*ASME – American Society of Mechanical Engineers Product style and configuration may vary.

MODEL: PXCMLC1683066