



EC-1-DV model is designed to accommodate multiple electrical requirements within one pump. The DV suffix indicates that the pump is capable of operating from a wide range of supply voltages to maintain consistent pump performance. Similar to our EC-1 model, this model includes improved noise reduction, reliable solid-state switching technology, and easy to install mounting brackets to create a pump that benefits contractors, installers, and end-users.

Item: 553507

Model: EC-1-DV

Ratings

Frequency	50/60 Hz
Amps - Full Load	0.18 A
Full Load Watts	18 W
Volts	110-240 VAC
Cord Length	5 ft
Continuous Duty	No
Maximum Flow Rate - 60Hz	0.05 gpm / 3 gph
Shut-Off	33 ft
Safety Switch	No

Liquid

Max Fluid Temperature	140 °F
-----------------------	--------

Materials of Construction

Material	No
----------	----

Installation

Discharge	0.25 "
Product Length	4.1 "
Product Width	1.8 "
Product Height	2.4 "
Pump Length	4.1 "
Product Weight	1 lb
Product Weight w/ Pack	1.75 lb
Carton Length	10.25 "
Carton Width	7.63 "
Carton Height	2.25 "
Tubing Included	No

Other

Electrical Agency Approvals	cCSAus
Standard Warranty	24 Months