



Potato Peeler PI-20

20 KG. / 44 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.
0-6 min. timer.
Removable plate for easy cleaning.**

High capacity and production owing to lateral stirrers covered with silicon carbide abrasive (approved by NSF). Aluminium base plate lined with silicon carbide abrasive (approved by NSF). Construction in stainless steel.

- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Liftable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stainless steel floor stand.
- Filter with no-foam feature.

TECHNICAL SPECIFICATIONS

Hourly production: 800 lbs. / 950 lbs.
Capacity per load: 44 lbs.
Timer (min-max): 0 ' - 6 '
Total loading: 0.75 Hp

Electrical supply: 120V / 60 Hz / 1~ (5 A)

External dimensions (WxDxH)

- Width: 17 "
- Depth: 25 "
- Height: 27.4 "

External dimensions with stand

- Width with stand: 17 "
- Depth with stand: 25.1 "
- Height with stand: 43.9 "

Net weight: 92.6 lbs.

