



SPECIALIST®

DRY LUBE

50-STATE
VOC
COMPLIANT

NSF

NOT EVEN THE HIGHEST TEMPERATURES POSE A PROBLEM WITH WD-40 Specialist® Dry Lube. Our spray, which is safe on multiple surface,* reduces friction while providing long-lasting lubrication and corrosion protection. It leaves no sticky residue, and resists dirt and dust.

TECHNICAL DATA SHEET

FEATURES

- Reduces friction and wear, and enhances performance
- Resists dirt and dust accumulation
- Working temperature range—up to 500°F

*Safe to use on most common application surfaces, including most metals, plastics, and rubbers, when used as directed.

APPLICATIONS

Blades and bits, tracks, slides, pulleys, hinges, machine parts, switches, conveyor belts, rollers, table saws, drills, lathes, and other power tools and equipment



Provides 2x the wear protection of most of the competition.¹



REDUCES FRICTION AND WEAR ON:



¹ Test Lab: WD-40 Co. Technical Center (Pine Brook, NJ) ASTM D4172 – Modified Duration (30 min); Test dates 1/2025-2/2025. Competitors tested: Super Lube® Dri-Film Lubricant, CRC® Dry Graphite Lube, CRC® Dry Moly Lube, B'laster® Industrial Graphite Dry Lubricant; B'laster® Advanced Dry Lube. B'laster® is a registered trademark of B'laster Chemical Company Inc. CRC® is a registered trademark of CRC Industries Inc. Super Lube® is a registered trademark of Kano Laboratories Inc.



ITEM #: 30005	NET WEIGHT: 10 OZ.	CASE ORDER #: 300059	CASE UNITS: 6/CASE
---------------	--------------------	----------------------	--------------------

No warnings for our products are required by California Proposition 65. Learn more at www.p65warnings.ca.gov

DRY LUBE PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (Initial):	90-140°C (194-284°F)
Solubility in Water:	Insoluble in water
Vapor Pressure:	40-50 psi @ 70°F
Percent Volatile:	>90%
Coefficient Of Water/ Oil Distribution:	Not Determined
Flashpoint:	<-29.2°F Tag Closed Cup

Specific Gravity:	0.72
pH:	Not Applicable
Vapor Density:	Greater than 1 (air=1)
VOC:	90.7%
Appearance/Odor:	Colorless. Pleasant Odor.
Flammable Limits:	LEL: 0.9% UEL: 9.5%



INTRODUCING THE WD-40® BRAND JOB DONE RIGHT® SYSTEM

EXPERIENCE A COMPREHENSIVE SOLUTION DESIGNED TO PROTECT YOUR EQUIPMENT AT EVERY STAGE.

This end-to-end approach ensures optimal performance, reduces the risk of failures, and keeps your machinery running smoothly.



Start every job with thorough preparation.



Clean your surface for optimal lubrication.



Experience superior performance with the best lubrication products on the market.



Safeguard your hard work with the trusted protection of the WD-40 Brand.

KNOWLEDGE BASE

For more detailed technical specifications and product data sheets, visit www.wd40.com/industrial

LEARN MORE

WE'RE HERE TO HELP

For product inquiries, technical assistance, or to place an order, please contact WD-40® Industrial Division at 1.888.324.7596 or www.wd40.com/contact-us

CONTACT US

