



Avantco Equipment

Item #: 177HWD10D Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco HWD10D 10 Gallon Bulk Hot Water Dispenser - 208/240V, 7,000W

Item #177HWD10D



Technical Data

Width	18 Inches
Depth	16 Inches
Height	26 Inches
Power Cord Length	70 7/8 Inches
Hertz	60 Hz
Phase	1 Phase
Voltage	208/240 Volts
Wattage	7000 Watts
Capacity	10 Gallons
Color	Silver

Features

- 10 gallon bulk capacity
- Dial thermometer for precise monitoring
- Reliable no-drip faucet prevents waste
- Stainless steel body for durability and a sleek look
- 208/240V, 7,000W

Certifications



6-50P



3/4" Water Connection



Certified by NSF



Technical Data

Control Type	Analog Dial
Features	NSF Certified
Material	Stainless Steel
Maximum Temperature	208 Degrees F
Plug Type	NEMA 6-50P
Power Type	Electric
Style	Automatic
Temperature Range	77 - 208 Degrees F
Type	Hot Water Dispensers
Usage	Standard Duty
Water Inlet Size	3/4 Inches

Notes & Details

This Avantco 10 gallon bulk hot water dispenser is perfect for times when you need a lot of hot water quickly or are setting up a hot beverage bar. Whether you are filling insulated beverage dispensers or individual tea cups, use this dispenser to make sure you never run out of hot water. This unit boasts an automatic refill system, ensuring you're never unprepared, while the indicator lights let you know when the unit is powered and heating.

The body of this hot water dispenser is made of stainless steel for a sleek-looking, durable product that will last through many uses while looking professional on your countertop. Additionally, it features a 10 gallon capacity and boasts 7,000W of power. It provides a convenient and affordable way to provide hot water to prepare hot chocolate, tea, and even soups and gravies.

This water dispenser features a dial thermometer for precise monitoring as well as a multi-setting thermostat with a hold setting. Plus, to prevent waste, it has a reliable no-drip faucet. A great choice for your restaurant or cafe, this dispenser requires a 208/240V electrical connection for operation.