

Item #: 178GDC15HCW Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco GDC-15-HC 25 5/8" White Swing Glass Door Merchandiser Refrigerator with LED Lighting

Item #178GDC15HCW



Technical Data

Width	25 5/8 Inches
Depth	22 7/8 Inches
Height	79 5/16 Inches
Power Cord Length	98 1/2 Inches
Interior Width	22 13/16 Inches
Shelf Width	22 1/4 Inches
Interior Depth	19 1/2 Inches
Shelf Depth	15 15/16 Inches
Interior Height	46 7/8 Inches
Amps	2.5 Amps

Features

- Anti-fog dual-pane tempered glass swing door with magnetic gaskets
- Interior LED lighting illuminates product; back lit exterior top panel attracts customers' attention
- 4 adjustable shelves with price tag strip on each shelf
- Easy to use digital temperature controls
- 115V; 1/3 hp compressor; R-290 refrigerant

Certifications



5-15P



Customizable




ETL Listed

Technical Data

Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	286 Watts
Access Type	Doors
BTU (LBP)	853 BTU
Capacity	13.5 cu. ft.
Capacity (per Shelf)	88 lb.
Color	White
Compressor Location	Bottom Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable LED Lighting
Hinge Location	Right
Horsepower	1/3 hp
Installation Type	Freestanding
Interior Color	White
Number of Doors	1 Doors
Number of Shelves	4 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	2.5 oz.
Refrigerant Type	R-290
Sections	1 Section
Starting Amps	7.5 Amps
Starting Wattage	858 Watts
Temperature Range	33 - 40 Degrees F
Type	Merchandising Refrigeration

Plan View





Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-15-HC 25 5/8" white merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek white finish and a lighted top graphics area. And, since the housing is made from white coated steel, you can be sure that it will provide superior durability. Additionally, it boasts an anti-fogging, dual-pane tempered glass swing door to ensure that customers always have a clear view of your products, while 4 epoxy-coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate changing inventory and menus. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 1/3 hp compressor that runs on R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include magnetic gaskets, automatic defrosting, and a digital temperature control with a digital display. The unit's narrow design is ideal for compact spaces, while adjustable leveling feet allow you to position it appropriately. Because it is narrow, the merchandiser is not compatible with casters to prevent it from falling over, thus ensuring safe installation and operation. This item requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.