

Item #: 178GDC69HCW Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco GDC-69-HC 78 1/4" White Swing Glass Door Merchandiser Refrigerator with LED Lighting

Item #178GDC69HCW



Technical Data

Width	78 1/4 Inches
Depth	30 Inches
Height	80 5/16 Inches
Power Cord Length	96 1/2 Inches
Interior Width	73 1/2 Inches
Left Door Opening Width	21 5/8 Inches
Left/Right Shelf Width	23 1/4 Inches
Middle Door Opening Width	22 1/16 Inches
Middle Shelf Width	25 13/16 Inches
Right Door Opening Width	21 5/8 Inches

Features

- Anti-fog dual-pane tempered glass swing doors with magnetic gaskets
- Interior LED lighting illuminates product; back lit exterior top panel attracts customers' attention
- 12 adjustable shelves with price tag strip on each shelf
- Easy to use digital temperature controls
- 115V; 4/5 hp compressor; R-290 refrigerant

Certifications



5-15P



Customizable




ETL Listed

Technical Data

Interior Depth	23 5/8 Inches
Shelf Depth	23 Inches
Interior Height	51 1/16 Inches
Amps	8.4 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	824 Watts
Access Type	Doors
BTU (LBP)	2040 BTU
Capacity	58.2 cu. ft.
Capacity (per Shelf)	88 lb.
Color	White
Compressor Location	Bottom Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable LED Lighting
Hinge Location	Left Right
Horsepower	4/5 hp
Installation Type	Freestanding
Interior Color	White
Number of Doors	3 Doors
Number of Shelves	12 Shelves
Plug Type	NEMA 5-15P
Refrigerant Capacity	3.9 oz.
Refrigerant Type	R-290
Sections	3 Sections
Starting Amps	25.2 Amps
Starting Wattage	2472 Watts
Temperature Range	33 - 40 Degrees F
Type	Merchandising Refrigeration

Plan View





Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-69-HC 78 1/4" white merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek white finish and a lighted top graphics area. And, since the housing is made from white coated steel, you can be sure that it will provide superior durability. Additionally, it boasts 3 anti-fogging, dual-pane tempered glass swing doors to ensure that customers always have a clear view of your products, while 12 epoxy-coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate changing inventory and menus. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 4/5 hp compressor that runs on R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include magnetic gaskets, automatic defrosting, and a digital temperature control. This item requires a 115V electrical connection for operation. This multi-door unit has one left hinge and two right hinges.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.