

Item #: 178GDICE24WC Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco GD-ICE-24F 31" White Glass Door Ice Merchandiser with Customizable Panel

Item #178GDICE24WC



Technical Data

Width	31 1/8 Inches
Depth	33 1/4 Inches
Height	86 13/16 Inches
Power Cord Length	98 1/2 Inches
Interior Width	25 3/16 Inches
Interior Depth	28 3/8 Inches
Opening Depth	62 7/8 Inches
Interior Height	62 Inches
Amps	4.9 Amps
Hertz	60 Hz

Features

- 1 self-closing, triple-pane, argon-filled, anti-fog swing glass door
- Temperature range: 18 to 25 degrees Fahrenheit
- Easy-to-use digital temperature controls; interior LED lighting
- Holds approximately (45) 8 lb. bags of ice
- 115V, 1 hp; R290 refrigerant; 4.9 Amps

Certifications



5-15P



Customizable



ETL Listed


Intertek

Avantco Refrigeration

Technical Data

Phase	1 Phase
Voltage	115 Volts
8 lb Bag Capacity	45 Bags
BTU (LBP)	1744 BTU
Capacity	22.625 cu. ft.
Compressor Location	Bottom Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable LED Lighting
Horsepower	1 hp
Number of Doors	1 Doors
Number of Shelves	1 Shelf
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Refrigeration Type	Auto Defrost
Temperature Range	18 - 25 Degrees F
Type	Ice Merchandisers
Usage	Indoor

Plan View



Notes & Details

Store and showcase your bagged ice offerings with this Avantco GD-ICE-24F 31" black customizable ice merchandiser! Designed with sharp looks and usability in mind, this unit is the perfect display for your bags of ice with its sleek finish. And, since the housing is made from white coated steel, you can be sure that it will provide superior durability. This unit boasts an anti-fogging glass swing door to ensure that customers always have a clear view of your products, while 4 epoxy coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate prepackaged foods in a variety of sizes. Interior LED lighting also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 18 to 25 degrees Fahrenheit, this freezer boasts a bottom-mounted 1 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the door, automatic defrosting, as well as a digital temperature control and display. This item requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.