



BLS-3HTD-2H

Half Size Ventless Hood LED/TOUCH Ovens




UL 710 Emissions



NEMA
6-15P
Plug

TOUCH digital programmable controls:



9

9 BAKING
STEPS



0 - inf
TIMER



120° - 500° F
TEMPERATURE



0-20-40-60-80-100%
HUMIDITY



2 FAN
SPEEDS



PROOFER
CONTROL



99 PROGRAMS



WI-FI



DATA DRIVEN
COOKING -
CHAIN BASED
APPLICATION



NEMA
6-20P
Plug



OST-34A-CS

Short Heavy-Duty Stand with Wheels for Half Size Ovens

- Handles 5 half size sheet pans (not included)
- Can hold 2 half size Cadco ovens with optional CXC651 Stacking Kit
- Aluminum



Made to Cadco specifications by UNOX S.p.A., Italy NSF, MET to UL & CSA Standards

Cadco Model XAFT-03HS-LD = UNOX Model XAFT-03HS-ELDV-US

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:

Model	Color	Volts	Watts	AMPS	Unit Dimensions
XAKHT-HCHS	Stainless	208/240	200	1	W: 23 5/8" H: 10 7/8" D: 28 25/32"
XAFT-03HS-TD	Stainless	208/240	3300	14	W: 23 5/8" H: 16 5/8" D: 29"
OST-034A-CS	Stainless	N/A	N/A	N/A	W: 23.87" H: 21.15" D: 27.01"

Shipping Unit Dimensions

Skid 1: 180lbs 40L x 40 W x 25 H

Skid 2: 195 Lbs 48 L x 40 W x 48 H

