

Item #: 6871518BPC Project: _____

Qty: _____ Date: _____ Approval: _____

Boltic 72" Black Powder Coat Air Curtain with Plunger Door Switch

Item #6871518BPC



Technical Data

Width	70 15/16 Inches
Depth	8 5/8 Inches
Height	10 1/4 Inches
Power Cord Length	59 Inches
Mounting Width	69 1/8 Inches
Amps	6.33 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Wattage	760 Watts

Features

- Internal room temperature is retained when external door opens
- Prevents pests from coming indoors
- Sleek black powder coat construction
- Maintains a low noise level at only 74-76 decibels
- Features 2 speeds and an adjustable air deflector; 120V

Certifications





Technical Data

Air Velocity	2559 - 3150 FPM
Airflow Rating	2354 - 2943 CFM
Color	Black
Installation Type	Surface Mounted
Material	Powder Coated Metal
Noise Level	74 - 76 dB
Plug Type	NEMA 5-15P
Speeds	2 Speed
Style	Back Door Drive-Thru Window Front Door
Type	Air Curtains

Notes & Details

Keep your air temperature controlled and free of pests with this Boltic air curtain! Whether your internal temperature needs to stay warm and heated or the AC needs to be kept inside, this air curtain is a great solution when entry points are exposed to the outdoor elements. Cutting down on the infiltration of outside air will save you money in climate-controlled areas. The blast of air has an air velocity of 2559-3150 FPM, making it an excellent repellent and helping to prevent unwanted pests from entering your establishment. It also maintains a low level of noise at only 74-76 decibels and will not disturb guests!

This air curtain is ideal for drive-thru windows, concession stands, building entrances, walk-in coolers, and patios. For added convenience, the plunger door switch releases when the door is opened, turning the air curtain on, and closes when the door is shut and the plunger is pushed in, turning the air curtain off. The black powder coating creates a hard finish, providing a sleek appearance and exceptional durability. This model includes an adjustable air deflector to direct the air in the direction you prefer, keeping it away from bothersome areas. It also features 2 different operating speeds to accommodate your needs. This unit requires a 120V electrical connection for operation. The door switch requires professional installation.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.