

Item #: 6873512LYB Project: _____

Qty: _____ Date: _____ Approval: _____

Boltic 48" Black Aluminum Air Curtain with Remote Magnetic Door Switch

Item #6873512LYB



Technical Data

Width	47 1/4 Inches
Depth	8 1/2 Inches
Height	9 1/16 Inches
Power Cord Length	59 Inches
Mounting Width	39 Inches
Amps	3.33 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Wattage	400 Watts

Features

- Internal room temperature is retained when external door opens
- Prevents pests from coming indoors
- Sleek black aluminum construction
- Maintains a low noise level at only 50-53 decibels
- Features 2 speeds and an adjustable air deflector; 120V

Certifications



5-15P



UL Certified

Technical Data

Air Velocity	2500 - 3150 FPM
Airflow Rating	706 - 883 CFM
Color	Black
Features	UL Certified
Installation Type	Surface Mounted
Material	Aluminum
Noise Level	50 - 53 dB
Plug Type	NEMA 5-15P
Speeds	2 Speed
Style	Back Door Drive-Thru Window Front Door
Type	Air Curtains

Notes & Details

Keep your air temperature controlled and free of pests with this Boltic air curtain! Whether your internal temperature needs to stay warm and heated or the AC needs to be kept inside, this air curtain is a great solution when entry points are exposed to the outdoor elements. Cutting down on the infiltration of outside air will save you money in climate-controlled areas. The blast of air has an air velocity of 2500-3150 FPM, making it an excellent repellent and helping to prevent unwanted pests from entering your establishment. It also maintains a low level of noise at only 50-53 decibels and will not disturb guests!

This air curtain is ideal for drive-thru windows, concession stands, building entrances, walk-in coolers, and patios. For added convenience, the remote magnetic door switch keeps the air curtain off when the door is closed and the magnet is engaged. When the door is opened, the unit turns on. The black aluminum construction will keep your establishment looking sleek, while providing exceptional durability. This model includes an adjustable air deflector to direct the air in the direction you prefer, keeping it away from bothersome areas. It also features 2 different operating speeds to accommodate your needs. This unit requires a 120V electrical connection for operation. The door switch requires professional installation.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.