

Item #: 687BFM1510SS Project: _____

Qty: _____ Date: _____ Approval: _____

Boltic 42" Stainless Steel Air Curtain with Plunger Door Switch

Item #687BFM1510SS



Technical Data

Width	39 3/8 Inches
Depth	8 5/16 Inches
Height	10 1/4 Inches
Power Cord Length	59 Inches
Mounting Width	33 1/2 Inches
Amps	3.33 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Wattage	400 Watts

Features

- Retains internal room temperature when external door opens
- Prevents pests from coming inside
- Sleek stainless steel construction
- Maintains a low noise level at only 69-71 decibels
- Features 2 speeds; 120V

Certifications



5-15P



UL Certified

Technical Data

Air Velocity	2559 - 3150 FPM
Airflow Rating	1354 - 1648 CFM
Color	Silver
Features	UL Certified
Installation Type	Surface Mounted
Material	Stainless Steel
Noise Level	69 - 71 dB
Plug Type	NEMA 5-15P
Speeds	2 Speed
Style	Back Door Drive-Thru Window Front Door
Type	Air Curtains

Notes & Details

Ensure your air temperature is controlled while keeping your entrance area free of pests with this Boltic 42" stainless steel air curtain with plunger door switch! Whether your internal temperature needs to stay warm and heated or the AC needs to be kept inside, this air curtain is a great solution for entry points exposed to outdoor elements. Reducing the infiltration of outside air will save you money in climate-controlled areas. The blast of air has an air velocity of 2,559 to 3,150 FPM, making it an excellent repellent and helping to prevent unwanted pests from entering your establishment. It also maintains a low level of noise at only 69 to 71 decibels and will not disturb guests!

This air curtain is ideal for drive-thru windows, concession stands, building entrances, walk-in coolers, and patios. For added convenience, the plunger door switch automatically turns the fan on and off when the door opens and closes. The easy-to-clean stainless steel design will keep your establishment looking sleek while providing exceptional durability. The air curtain also features 2 different operating speeds to accommodate your needs. This unit requires a 120V electrical connection for operation. The door switch requires professional installation.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.