

Item #: 73AVF7500 Project: _____

Qty: _____ Date: _____ Approval: _____

Boltic Electric Ceiling-Mounted Garage / Unit Heater - 240V, 7,500W

Item #73AVF7500



Technical Data

Width	14 Inches
Depth	10 5/8 Inches
Height	12 1/2 Inches
Amps	31.3 Amps
Voltage	240 Volts
Wattage	5000 - 7500 Watts
Color	Black
Coverage Area	1500 sq. ft.
Included	Mounting Hardware
Mounting Style	Ceiling

Features

- Compact design saves space
- 1 fan-only setting and 2 heat settings with temperature range from 50-95 degrees Fahrenheit
- Built-in adjustable thermostat with easy-to-use timer and remote control (batteries sold separately)
- Adjustable design with 3 installation angles and 4 louvers to direct airflow
- Coverage area of 1,500 sq. ft.

Certifications



Hardwired



ETL Listed

Intertek

Technical Data

Features	Adjustable Electronic Thermostat Remote Control Timer
Noise Level	55 dBA
Number of Heat Settings	2 Settings
Plug Type	Hardwire
Power Type	Electric
Temperature Range	50 - 95 Degrees F
Total BTU	25589 BTU
Type	Heaters

Notes & Details

Provide reliable heating to your commercial or industrial workspace with this Boltic electric garage / unit heater. This versatile, ceiling-mounted heater features 1 fan-only setting as well as 2 heat settings that range from 50-95 degrees Fahrenheit at 5,000-7,500W, with a maximum heat production of up to 25,589 BTU per hour. This unit heater is designed to efficiently heat areas while taking up minimal space, and it includes a convenient remote control (batteries sold separately) that can be used up to 19 3/4' away from the unit with no obstructions. This item operates at a noise level below 55 dBA, it requires a 240V connection for operation, and it's ideal for commercial locations like garages and workshops.

This compact garage heater is designed to provide both horizontal and vertical air flow with 4 individual, adjustable louvers that direct the flow of air up or down and a coverage area of 1,500 sq. ft. It includes a mounting bracket with hardware, and it can be installed at a 90-degree, 67.5-degree, or 45-degree vertical angle for maximum coverage to ensure comfort for customers and staff. This heater features a built-in, adjustable thermostat, a control panel with an LCD screen, and a timer with settings from 1-8 hours. It also features a caution indicator, a thermal cut-out safety feature to prevent overheating for added safety, and a power selection switch.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.