

All 3 phase motors now VFD compatible!



CANARM BRANDED AC TEFC MOTORS

You Know Canarm as Canada's leading manufacturer of Ventilation equipment.

Canarm also imports a number of competitively priced Electric motors that are ideal for use on axial fans and blowers.

Canarm electric motors are available in a variety of horsepower ranges and frame sizes to fit your application.

All motors are CSA approved for use in Canada and the United States.



FEATURES

- Totally enclosed fan cooled (TEFC) or open drip proof (DDP)
- Ball bearing
- Thermally protected (where indicated below).
- F Class insulation.
- 40°C ambient temperature rated
- Available in single or three phase
- Single speed only
- All 3 phase units now VFD compatible

PERFORMANCE SPECIFICATIONS

Canarm Model #	HP	PH	RPM	VOLTS	Frame	ENCL	SF	HZ	Capacitor (Run or Start or CSCR)	Thermal Protection	Mount	Premium Efficiency	CSA/CSAus
SINGLE PHASE TEFC													
1M111-C	1/3	1	1800	115/230V	56C	TEFC	1.15	60	CSCR	MANUAL	Rigid Base + C-Face	NO	CSA/CUS
1M112-C	1/2	1	1800	115/230V	56C	TEFC	1.15	60	CSCR	MANUAL	Rigid Base + C-Face	NO	CSA/CUS
1M113-C	3/4	1	1800	115/230V	56C	TEFC	1.15	60	CSCR	MANUAL	Rigid Base + C-Face	NO	CSA/CUS
1M114-C	1	1	1800	115/230V	56C	TEFC	1.15	60	CSCR	MANUAL	Rigid Base + C-Face	NO	CSA/CUS
1M115-C	1.5	1	1800	115/230V	56C	TEFC	1.15	60	CSCR	MANUAL	Rigid Base + C-Face	NO	CSA/CUS
1M116-C	2	1	1800	115/230V	56HC	TEFC	1.15	60	CSCR	MANUAL	Rigid Base	NO	CSA/CUS
1M117-C	3	1	1800	208-230V	182T	TEFC	1.15	60	CSCR	MANUAL	Rigid Base	NO	CSA/CUS
1M118W-C	5	1	1800	208-230V	184T	TEFC	1.15	60	CSCR	NO	Rigid Base	NO	CSA/CUS
1M119-C	7.5	1	1800	208-230V	213T	TEFC	1.15	60	CSCR	NO	Rigid Base	NO	CSA/CUS
1M120-C	10	1	1800	208-230V	215T	TEFC	1.15	60	CSCR	NO	Rigid Base	NO	CSA/CUS
ODP MOTORS 60 HZ													
1MD008-C	1/8	1	1800	115/230	48	ODP	1	60	RUN	AUTO	T Bolt and Rigid Base	NO	CSA/CUS
1MD110-C	1/4	1	1800	115/230	48	ODP	1	60	RUN	AUTO	T Bolt and Rigid Base	NO	CSA/CUS
1MD111-C	1/3	1	1800	115/230	48	ODP	1	60	RUN	AUTO	T Bolt and Rigid Base	NO	CSA/CUS
1MD112-48	1/2	1	1800	115/230	48	ODP	1	60	RUN	AUTO	T Bolt and Rigid Base	NO	CSA/CUS
1MD113-48	3/4	1	1800	115/230	48	ODP	1	60	RUN	AUTO	T Bolt and Rigid Base	NO	CSA/CUS
1MD114-C	1	1	1800	115/208-230	56	ODP	1.15	60	CSCR	MANUAL	C-Face and Rigid Base	NO	CSA/CUS
1MD115-C	1.5	1	1800	115/208-230	56	ODP	1.15	60	CSCR	MANUAL	C-Face and Rigid Base	NO	CSA/CUS
1MD116-C	2	1	1800	115/208-230	56	ODP	1.15	60	CSCR	MANUAL	C-Face and Rigid Base	NO	CSA/CUS
VFD COMPATIBLE 3 PHASE MOTORS													
3M211-V	1/3	3	1800	230/460V	56C	TEFC	1.15	60	NO	NO	Rigid Base + C-Face	NO	CSA/CUS
3M212-V	1/2	3	1800	230/460V	56C	TEFC	1.15	60	NO	NO	Rigid Base + C-Face	NO	CSA/CUS
3M213-V	3/4	3	1800	230/460V	56C	TEFC	1.15	60	NO	NO	Rigid Base + C-Face	NO	CSA/CUS
3M214-V	1	3	1800	230/460V	56HC	TEFC	1.15	60	NO	NO	Rigid Base + C-Face	NO	CSA/CUS
3M215-V	1.5	3	1800	208-230/460V	56	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC
3M216-V	2	3	1800	208-230/460V	56	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC
3M217-V	3	3	1800	208-230/460V	182T	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC
3M218-V	5	3	1800	208-230/460V	184T	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC
3M219-V	7.5	3	1800	208-230/460V	213T	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC
3M220-V	10	3	1800	208-230/460V	215T	TEFC	1.15	60	NO	NO	Rigid Base	YES	CSA/CUS/CC

WARRANTY

- 1 year warranty