

SC JOHNSON PROFESSIONAL® EZ CARE FLOOR COATING

EZ Care is an integrated floor care system suitable for a variety of substrates that allows you to achieve a durable, high-gloss finish in no more than four coats and eliminates the manual process of conventional stripping.

THE EZ CARE Floor Coating is a versatile and unique finish that uses a proprietary polymer-blend formulation making it easy to apply and can be easily removed using the EZ Care Floor Coating Remover and an auto scrubber.

DOES NOT CONTAIN INTENTIONALLY ADDED PFAS* OR PHTHALATES.



EZ Care Floor Coating is part of the EZ CARE floor care system and is specifically designed to be used along with SC Johnson Professional® EZ CARE Floor Coating Remover, EZ CARE Heavy Duty Scrub Pads, and EZ CARE High Speed Conditioning and Polish pad.

THE EZ CARE Floor Coating is a versatile and unique finish that uses a proprietary polymer-blend formulation making it easy to apply and can be easily removed using the EZ Care Floor Coating Remover and an auto scrubber.

- Only 4 coats needed to achieve a durable high-gloss appearance. Extremely tough, highly repairable and does not require a conventional floor stripper to be removed.
- Goes on smoothly and evenly with any application method.
- Gloss levels are retained with or without the need of multispeed burnishing.
- Up to 4 coats can be easily removed in one pass using the EZ Care Floor Coating Remover and an auto scrubber – **no conventional stripping chemicals needed.**
- Has a light fresh scent.

SKU	DESCRIPTION	CASE PACK	IN USE GALLONS PER CARTRIDGE
362823	5-Gallon (640 FL OZ) 18.9L Bag in Box	1	Ready-to-Use

*PFAS are perfluoroalkyl and polyfluoroalkyl substances, which are a class of fluorinated organic chemicals containing at least one fully fluorinated carbon atom.

Use Instructions:

Place proper warning blockades around work area. **(Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.)**

FLOOR PREPARATION:

1. STRIP THE EXISTING FLOOR COATING using SC Johnson Professional® Hyper Concentrate Floor Stripper, per label instructions. Once on the EZ CARE system you will never need to conventionally strip again.

2. USING A HIGH-SPEED MACHINE, (1500+RPM) burnish the bare floor with the EZ CARE High Speed Conditioning and Polish Pad. In an overlapping method, burnish the substrate a minimum of 2 passes. Ensure debris or particulates are removed via dust mop or rinsing technique prior to applying floor coating.

- Note: The EZ CARE High Speed Conditioning & Polish pad is not designed to be used on linoleum, ceramic, sheet vinyl, vinyl asbestos, cork and rubber. Refer to pad instructions for use.

FLOOR COATING APPLICATION:

Apply 2-4 coats of coating using a clean mop or applicator. Allow approximately 30 minutes dry time between coats. Temperature, humidity, and air circulation may affect drying time. Allow 24 hours cure time before maintenance.

MAINTENANCE CLEANING:

Dust mop or sweep area as needed to be maintained. For best results regularly clean floors using SC Johnson Professional® Multi-Surface Neutral Floor Cleaner as directed and the EZ CARE Heavy Duty Scrub Pad if using an auto-scrubber.

BURNISHING:

SC Johnson Professional® EZ CARE Floor Coating is uniquely formulated to allow for dry buffing or UHS burnishing with a wide range of different pads and machines to achieve the desired appearance. Refer to the flooring manufacturer's maintenance guide for recommended pad.

REMOVE AND RECOAT:

You may also use the **SC Johnson Professional® Hyper-concentrated Floor Stripper**. Please follow label instructions.

SAFETY PRACTICES TO FOLLOW

It's good business practice to assure that your employees have read and understood the product labels and Safety Data Sheet before using this product. The label use directions and SDS contain important hazard warnings, precautionary statements and first aid procedures. This information is available on-line at www.scjp.com or by calling 1-800-248-7190 in the US and 1-888-362-7267 in Canada.

FOR BEST RESULTS DO NOT DILUTE. Best to apply in a well-ventilated area. Do not apply on surfaces with temperatures below 50°F (10°C). Not intended for outdoor spaces. Not intended for use on wood. Test, in an inconspicuous area, for adhesion on concrete, polished concrete and highly polished marble and granite.

INGREDIENTS:

Water (7732-18-5); Acrylic Polymers (Proprietary); Ethoxydiglycol (111-90-0); Trimethyl Pentanyl Diisobutyrate (6846-50-0); POLYACRYLATE-15 (67892-91-5); 2-Propenoic acid, polymer with ethenylbenzene, butyl 2-propenoate and (1-methylethenyl)benzene, ammonium salt (360564-31-4); Tributoxyethyl Phosphate (78-51-3); 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene, ammonium salt (89678-90-0); Zinc Ammonium Carbonate (38714-47-5); Hexoxyethanol (112-25-4); Fragrance (Proprietary); UNDECETH-5 (34398-01-1); Caprylyl Pyrrolidone (2687-94-7); Pentasodium Pentetate (140-01-2). Contains trace amounts of phosphorous.

PRODUCT SPECIFICATION

Color	White
pH	8.2
Specific gravity	1.035 g/cm ³
Fragrance	Fresh Scent
Substrate compatability	VCT, LVT, Vinyl Asphalt, Vinyl Asbestos, Sheet Vinyl, Rubber, Lineoleum, Terrazzo, Honed Marble, Honed Granite, Natural Stone, Brick, Slate, Quarry Tile. Meets ASTM D-2047 for slip resistance.
incompatible materials	Do not mix with bleach or any other household cleaners. Strong bases.



SAY GOODBYE TO CONVENTIONAL STRIPPING

Contact your SC Johnson Professional sales representative and discover the EZ way to achieve a durable, high-gloss finish and eliminate the conventional stripping process.

SC Johnson Professional USA, Inc.
Charlotte, NC 28217

SC Johnson Professional CA Inc.
Brantford, ON N3T 5R1

www.scjp.com

scJohnson
PROFESSIONAL
A family company®