

E24 Series Heavy-Duty Electric Griddles

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approved _____
 Date _____

Models

- E24-24G • E24-48G • E24-72G
- E24-36G • E24-60G



Model E24-36G

Standard Features

- Stainless steel front and sides
- 4" (102mm) stainless steel legs
- Recovery signal light
- 3/4" (19mm) thick griddle plate
- 4-1/8" (105mm) front grease trough
- 3-sided splashguard
- 100°F (35°C) to 450°F (235°C) hydraulic thermostat with indicator light per each 12" width of griddle
- One-year limited parts & labor warranty (USA & Canada only)

Options & Accessories

- Stainless steel back
- Grooved griddle plate, in 12" (305mm) sections
- 460 volt (for complete amperage draws contact factory)
- Stands are available

Specifications

Heavy-duty electric griddles available in five widths; 24" (610mm), 36" (914mm), 48" (1219mm), 60" (1524mm) and 72" (1829mm).

High-performance, high-volume production with even, consistent, controlled temperatures.

3/4" (19mm) thick griddle plate complete with front grease trough and splashguard.

Optional grooved griddle tops in 12" (305mm) wide sections.

All models are designed as freestanding units or bank with other E24 series equipment.

Stainless steel front and sides.

100°F (35°C) to 450° F (235° C) hydraulic thermostats for each 12" (305) width of griddle surface.



E24 Series Heavy Duty Electric Griddles

7-1/4" [184mm]
REAR CABLE ENTRANCE

29-1/4" [743mm]

23-1/4" [591mm]

Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only.

Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.


4-1/8" [105mm]

1-7/8" [48mm]

12-13/16" [325mm]

10-3/4" [273mm]

NOTE: Add 4" (102mm) to height if sanitary legs are used.



Loading Chart

Model	Total Kw Load	Nominal Amperes Per Line										
		3 Phase									Single Phase	
		240V			208V			480V			240V	208V
		X	Y	Z	X	Y	Z	X	Y	Z	480V	
E24-24G	8.0	16.5	16.5	29.0	19.0	19.0	33.0	8.3	8.3	14.4	33.5	38.5
E24-36G	12.0	29.0	29.0	29.0	33.5	33.5	33.5	14.4	14.4	14.4	50.0	58.0
E24-48G	16.0	44.0	29.0	44.0	51.0	33.0	51.0	22.0	14.4	22.0	67.0	77.0
E24-60G	20.0	44.0	44.0	58.0	51.0	51.0	66.5	22.0	22.0	28.9	83.5	96.0
E24-72G	24.0	58.0	58.0	58.0	66.0	66.0	66.0	28.9	28.9	28.9	100.0	116.0

Export voltage available on request – Specify wiring required

kW loadings are reduced on 220 volt systems.

Standard wiring 240 volt (220/240) or 208 volt (197/219) single or three phase – Specify which is required

Surface Capacities

Model	Meat Patties 3-1/2 Oz (98g) (350°F/177°F)		Fried Eggs (300°F/149°C)		Minute Stakes 4 oz. (112g) (350°F/177°C)		Pancakes 4" (101mm) Dia. (400°F/204°C)	
	Load	Hourly	Load	Hourly	Load	Hourly	Load	Hourly
E24-24G	33	300	27	613	27	267	31	460
E24-36G	50	450	40	920	40	400	46	690
E24-48G	67	600	53	1227	53	533	61	920
E24-60G	83	750	67	1533	67	667	77	1150
E24-72G	100	900	80	1840	80	800	92	1380

Model	W
E24-24G	24" (610mm)
E24-36G	36" (914mm)
E24-48G	48" (1219mm)
E24-60G	60" (1524mm)
E24-72G	72" (1829mm)

Installation Clearances	
Side	Rear
1" (25mm)	1-1/2" (38mm)

Garland reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
6836C
05/26

