

U.S. Range

Heavy-Duty Gas Radiant Charbroiler w/Adjustable or Non-Adjustable Grates

Project _____
Item _____
Quantity _____
CSI Section 11400
Approved _____
Date _____

Models

- UTBG24-AR24
- UTBG36-AR36
- UTBG48-AR48
- UTBG60-AR60
- UTBG24-NR24
- UTBG36-NR36
- UTBG48-NR48
- UTBG60-NR60
- UTBG72-NR72



Model UTBG24-AR24

Standard Features

- Stainless steel front, sides and back
- 4" stainless steel adjustable legs
- 3/4" NPT gas regulator on all 24" to 60" wide models with "T" gas manifold connection for straight through rear or flush-mount gas connections.
- 1" NPT gas regulator for GTBG72-NR72 model only. Has "T" gas manifold connection for straight through or nearly flush-mount gas connections.
- Stainless steel front rail; 4" (102mm) deep overall with 3 1/2" (89mm) top work surface
- Stainless steel large capacity crumb tray
- Reversible cast-iron broiler racks in 3" wide sections with 1/8" and 3/16" brand marks.
- 21-3/16" (538mm) broiling grid depth
- 2-position adjustable broiler grates or fixed-position non-adjustable grates
- One cast-iron radiant over a 18,000 BTU stainless steel burner for every 6" of broiler width.
- One 2-position hi/lo valve control for each burner.

Options & Accessories

- Stainless steel skirt for dais/counter surface mounting. The stainless steel skirt will reduce overall unit height by 1-3/4" (44.45mm).
- Stainless steel spatter-guard
- Removable wire holding shelf for spatter guards available for 24" and 36" models
- Broiler grate cleaning tool
- Fajita broiling grate: 9" wide, replaces 3 standard grate sections on the left or right end of the broiler. Limit one per broiler.
- Stainless stand with solid top and holding shelves, and adjustable feet
- Stainless stand with solid top and holding shelves, and casters, (locking front)
- Set of reversible cast-iron broiler racks with four brand marks per 3" section. Brand 3/16" wide.
- Removable stainless steel attachment condiment rail with universal 1/9 or 1/3 food pan cut outs (pans supplied by others)

Specifications

US Range gas radiant broilers are available with adjustable or non-adjustable cooking racks, in five nominal imperial widths from 24"(600mm) to 60"(1500mm) and with model UTBG72-NR72 only 72"(1800mm), 13" (330mm) high and 32" (814mm) deep.

Reversible cast-iron grates in 3" (76mm) wide sections overall cooking area depth 21 3/16" (538 mm).

One 18,000 BTU burner with individual valve control per 6" of broiler width.

Large stainless steel catch tray, stainless steel front, sides, and back.



Heavy-Duty Gas Radiant Charbroiler

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
6973A
05/25



U.S. Range

Heavy-Duty Gas Radiant Charbroiler

3.3" [84mm] DIVIDER ON
UTBG48-AR48 AND UTBG60-AR60
ADJUSTABLE BROILERS

* PLEASE ADD 7" [178mm] IN OVERALL DEPTH WITH
ATTACHMENT CONDIMENT RAIL OPTION

WIDTH

15-15/16" [404mm]

4" [102mm]

For use with Natural or Propane gas only. Gas input ratings shown for installations up to 2000 ft. (610m), above sea level. Please specify altitudes over 2000 ft. and gas type when ordering.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only.

Garland/U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Model #	Width In (mm)	Height (w/std legs)	Depth In (mm)	Total Input (BTU)	Shipping Information	
					Lbs/Kg	Cu Ft
With Adjustable Grates						
UTBG24-AR24	23-5/8 (600)	13 (330)	32 (814)	72,000	283/129	19
UTBG36-AR36	35-7/16 (900)			108,000	391/178	26
UTBG48-AR48	47-1/4 (1200)			144,000	514/283	34
UTBG60-AR60	59-1/16 (1500)			180,000	635/288	41
With Non-Adjustable Grates						
UTBG24-NR24	23-5/8 (600)	13 (330)	32 (814)	72,000	283/129	18
UTBG36-NR36	35-7/16 (900)			108,000	391/178	25
UTBG48-NR48	47-1/4 (1200)			144,000	514/283	33
UTBG60-NR60	59-1/16 (1500)			180,000	635/288	40
UTBG72-NR72	70 7/8(1800)			216,000	690/313	47

Supply Operating Pressure				Manifold Operating Pressure				Installation Clearances
Natural Gas		Propane		Natural Gas		Propane		
"WC	MBar	"WC	Mbar	"WC	MBar	"WC	Mbar	
7	17.5	11	27.5	4.5	11	10	24.5	

Gas Connection Options For Model
GTBG72-NR72 Straight (STD) Or Nearly
Flush 1" N.P.T Rear Gas Inlet w/Regulator.

Non-Adjustable Grate

Adjustable Grate

Garland reserves the right to make changes to the design or specifications without prior notice.