

HEAD PROTECTION

BRIGGS

NON-VENTED CAP

FEATURES

- Non Vented Meets ANSI Z89.1-2014 REQUIREMENTS FOR TYPE 1 CLASS E.
- Perforated synthetic leather comfort dome with molded EVA foam insert for additional shock absorbing protection.
- Oversized ratcheting fitment dial to adjust size, easy to grip and use with gloves on.
- 4-Point Suspension System for impact absorption.
- Adjustable chin strap for secure fit and increased protection.
- Available in vented or non vented versions.
- Supports face shields and ear-muff mounts.
- Can be worn forward or reversed.

MATERIAL

- High-density polyethylene (HDPE) with UV inhibitor.

CERTIFICATIONS

- ANSI Z89.1-2014 REQUIREMENTS FOR TYPE 1 CLASS E

APPLICATIONS OF USE

- Lineworker, Confined Space, Heavy Industrial, Rescue, Electrical, Oil and Gas, and General Construction.

LIFESPAN

- Hard hat lifespan may vary depending on the conditions of each work site. Hard hats subjected to more wear and tear or used outdoors in direct sunlight may need to be replaced more frequently. Daily inspections are the best way to determine when to replace a hard hat shell, suspension, or the entire unit. Suggested replacement is based on service life (Based on when the hard hat was placed into service, not the manufacture date).
- As a general guideline we recommend replacing hard hats every five years regardless of outside appearance, but this can vary due to use and job site conditions

ANSI DESCRIPTION

- Three classes indicate a helmet's electrical insulation rating relative to ANSI/ ISEA Z89.1-2014 standards: Class E (electrical) tested to 20,000 volts, Class G (general) tested to 2,200 volts, and Class C (conductive) that provides no electrical protection. However, these voltage ratings are not intended as an indication of the voltage at which the helmet protects the wearer.

SIZING

- One Size Fits Most
- Head Size 6 1/2 - 8 in
- Head Size 52-64 cm

HELMET WEIGHT

- Non-Vented Cap: 0.03 kg / 1.087 lbs

TEMPERATURE OF USE

- -30° C / +50° C
- -22° F / + 122° F



SHIPPING DIMENSIONS

- Single Unit: 10.75 L x 8.5 W x 7 H inches
- 1.087 lbs | 0.039 kgs
- Master Packing (30 Units): 59 L x 50 W x 70 H inches
- 32.61 lbs | 14.79 kgs

WARRANTY INFORMATION

- 1-Year Limited Warranty
- Every LIFT Safety product is covered by a one-year (from date of purchase) warranty on manufacturing defects when purchased new from an authorized LIFT Safety Dealer. eBay sellers and other sellers may not be considered authorized LIFT Safety dealer sellers.
- Learn more at warranty.liftsafety.com

COLOR	PART #	UPC CODE
YELLOW	HBSE-7L	879501009443
ORANGE	HBSE-7O	879501009306
HI-VIZ YELLOW	HBSE-20HV	680576353382
HI-VIZ ORANGE	HBSE-20HO	680576353429
WHITE	HBSE-7W	879501009320
GREY	HBSE-7Y	879501009344
BLUE	HBSE-7B	879501009467