



Project _____

Item 541UH30KIT17 Quantity _____

Approval _____ Date _____

MainStreet Equipment HTUC High-Temperature Undercounter Dishwasher with 18" Adjustable Stand - 208/240V, 1 Phase

Item #541UH30KIT17

Special Features

- Sleek, durable stainless steel with 2 dish racks
- Efficient unit uses only 0.53 gallons of water per rack
- Cleans up to 22 racks or 792 dishes per hour
- Built-in 3kW booster heater for proper rinse temperatures
- 18" adjustable stand reduces bending and back strain

Technical Data

Width	24 3/16 Inches
Depth	24 13/16 Inches
Height	32 11/16 Inches
Power Cord Length	6 Feet
Rack Length	20 Inches
Rack Width	20 Inches
Stand Height	17 11/16 - 18 11/16 Inches
Hertz	60 Hz
Phase	1 Phase
Voltage	208/240 Volts



Certifications



3/4" Water
Connection



6-20P



Intertek

ETL Listed

Technical Data

Booster Tank Capacity	1.9 gal.
Booster Wattage	3 Kilowatts
Dishes (per Hour)	792 Dishes
Features	Adjustable Booster Heater Included Built-In Detergent and Rinse Aid Dispenser Built-In Drain Pump Stand Included
High or Low Temp	High Temp
Horsepower	3/4 hp
Interior Clearance	15 1/4 Inches
Material	Stainless Steel
Number of Wash Cycles	1 Wash Cycle
Plug Type	NEMA 6-20P
Racks (per Hour)	22
Style	Undercounter
Wash Cycle Time	120 Seconds
Wash Pump Wattage	3 Kilowatts
Wash Tank Capacity	5.4 gal.
Water Inlet Size	3/4 Inches
Water Temperature	140 - 180 Degrees F

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.