

#495HTDT513

Approval: _____ Date: _____



- Simple top-mounted digital display and control panel
- 17" pillarless opening provides easy loading and unloading
- 4-sided door design saves energy by retaining heat
- Designed for straight-through or corner operation
- Recirculating design uses less water and energy than fill-and-dump models

 Hardwired
 3/4" Water Connection

 Field Convertible (Electrical)
 Certified by NSF

 Energy Star Qualified
 UL Certified

Width	28 1/2 Inches
Depth	32 1/16 Inches
Dishwasher Height	Standard
Height (Closed)	62 15/16 Inches
Height (Open)	82 1/16 Inches
Amps	35 Amps
Hertz	60 Hz
Phase	3 Phase
Voltage	208/240 Volts
Application	Dishwashers

Technical Data	
Dishwasher Style	Straight / Corner
Features	Adjustable Height Auto Fill Booster Heater Included Built-In Drain Pump Digital Display Energy Star Qualified Field-Convertible (Electrical) NSF Certified UL Certified
High or Low Temp	High Temp
Minimum Water Inlet Temperature	110 Degrees F
Number of Cycles	1 Cycle
Plug Type	Hardwire
Product Type	Dishwashers Warewashing Chemicals
Racks (per Hour)	51
Type	Single Rack
Wash Cycle Time	60 - 360 Seconds
Wash Tank Capacity	7.9 gal.
Water Inlet Size	3/4 Inches
Water Temperature	150 - 180 Degrees F
Water Usage	0.73 Gallons Per Rack

Notes & Details

Get spotless dishes every time with this Noble Warewashing high-temperature dishwasher. This dishwasher uses hot water to quickly sanitize dishes and wash away residue such as grease, baked-on food, and lipstick. It uses only 0.73 gallons of water per rack with a standard cycle that can be extended. When used with a chemical pump (sold separately), it can clean up to 51 racks per hour. This dishwasher features an electric booster heater to ensure that it reaches the proper temperature quickly. Its recirculating wash tank uses less water and energy than traditional fill-and-dump models.

This dishwasher is easy to use with a top-mounted digital display and simple control panel. It includes integrated wash and rinse arms with both tri-arm and single arm designs for greater coverage. It features a pumped rinse system to boost water pressure and provide efficient rinsing of dishes and glassware. This unit also has an automatic pumped drain to remove wash and rinse water at the end of each cycle. Its delime cycle eliminates hard water deposits that can cause damage to this dishwasher, making it easy to maintain and keep clean.

The dishwasher's 4-sided door saves energy by retaining heat. Its 17" pillarless opening ensures easy loading and unloading and can accommodate a single sheet pan. This unit ships for straight-through operation but can be converted to corner operation in the field. It has adjustable legs for use at your desired height. Its motor comes with thermal overload protection for safe use. This dishwasher requires a 208/240V, 3 phase electrical connection for operation, but it is field convertible to a 1-phase unit.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.