



Item# _____

Job _____



Rack

Model RD78N

13.56



RD78N

METRO MOBILE ADJUSTABLE RACK

- **Material:** Special design, natural finish, high-strength, extruded aluminum (6063-T6 alloy).
- **Rugged:** Aircraft-riveted construction throughout provides additional strength. Reinforced corner angles.
- **Adjustable Slides:** Keyholes in uprights on 1½" (38mm) spacing. Ideal for holding a variety of items of different sizes at different times.
- **Pass-Thru Design:** Can be loaded on one side and unloaded from the other for maximum efficiency and convenience.
- **13 Sets of "Vari-Slides":** Accommodate all popular modules used in the foodservice industry. Made of special extrusion (.100" or 2.5 mm thick) with bending support design for heavy loads.
- **Transport or Storage**
- **Refrigerator or Freezer**



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705


Copyright © 2020 InterMetro Industries Corp.



RD78N Rack

SPECIFICATIONS

- **Material:** Special design, natural finish, high-strength, extruded $\frac{1}{8}$ " (3.1mm) thick aluminum (6063-T6 alloy).
- **Construction:** Pass-thru design, aircraft-riveted construction throughout.
- **Top & Bottom:** $1\frac{1}{2}$ " x $1\frac{1}{2}$ " x $\frac{1}{8}$ " (38 x 38 x 3.1mm) angle-shape riveted to four corner posts. Closed bottom.
- **Corner Posts:** $1\frac{1}{2}$ " x $1\frac{1}{2}$ " x $\frac{1}{8}$ " (38 x 38 x 3.1mm) angle-shape.
- **Slides:** 3" x $4\frac{1}{2}$ " x .100" (76 x 114 x 2.5mm) extruded "vari-slides", with top, center and bottom slides riveted in place, remaining 10 sets adjustable on minimum 3" (76mm) centers. $\frac{1}{2}$ " (12mm) diameter stabilizer rod positioned at center, front and back.
- **Casters:** Two B5DN on back -5" (127mm) double ball bearing swivel, ball bearing axle, nickel-plated, donut neoprene-tired, pre-lubricated, bolted through separate full-length, angle-formed, $\frac{1}{8}$ " (3.1mm) thick aluminum plates to bottom of chassis. Two B5DNB on front—same as above, with wheel brake.



DIMENSIONS:

Model No.	Height		Width		Depth		Inside Height		Pan Capacity with (13) standard sets of slides on $4\frac{1}{2}$ " (114mm) centers*				Approx. Pkd Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	no.	size (in.)	no.	size (in.)	(lbs.)	(kg)
RD78N	69 $\frac{1}{2}$	1765	24 $\frac{3}{8}$	620	26	660	60 $\frac{1}{4}$	1530	26	10 $\frac{7}{8}$ x 19 $\frac{3}{4}$	13	15 x 20	93	42
									26	11 $\frac{1}{8}$ x 20	13	18 x 26		
									26	12 x 18	13	20 x 20		
									26	12 x 20	13	20 x 22		
									26	13 x 18	13	20 x 24		
									24	14 x 18				

ACCESSORIES:

Model	
A33	Gray Continuous Bumper
A37	Gray Corner Bumpers
A71	Floor Lock
A121	Extra Vari-Slides (will take 5 extra pair max.)

Manufactured by:

InterMetro Industries Corp.

North Washington Street
Wilkes-Barre, PA 18705

Phone 570-825-2741

FAX 570-825-2852

For Product Information, call 1-800-433-2232

For Customer Service, call 1-800-992-1776

InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705

L02-078

Rev. 9/20

Printed in U.S.A.

Information and specifications are subject to change
without notice. Please confirm at time of order.