



Regency 1.2 GPM Wall-Mount Faucet with 4" Centers and 3 1/2" Swivel Gooseneck Spout

#600FW44G12



Technical Data

|                |                                |
|----------------|--------------------------------|
| Spout Length   | 3 1/2 Inches                   |
| Faucet Height  | 8 Inches                       |
| Cartridge Type | Ceramic                        |
| Faucet Centers | 4 Inches                       |
| Features       | BPI Certified<br>NSF Certified |
| Finish         | Chrome                         |
| Flow Rate      | 1.2 GPM                        |
| Handle Type    | Lever                          |
| Material       | Brass                          |

Features

- 3 1/2" gooseneck spout with 1.2 GPM aerator
- Features 4" adjustable centers and 1/2" NPSM inlets
- Wall-mounted base with attractive chrome-plated brass construction
- Comes with a quarter turn brass ceramic cartridge
- 2 zinc handles

Certifications



1/2" Water Connection



Certified by NSF

Technical Data

|                       |                    |
|-----------------------|--------------------|
| Mounting Style        | Wall Mounted       |
| Mounting Type         | Workboard          |
| Plug Type             | NEMA L6-30P        |
| Pressure Rating       | 60 PSI             |
| Rough In              | 4 Inches           |
| Spout Clearance       | 5 5/8 Inches       |
| Spout Connection Size | 1"-20 UNEF         |
| Spout Type            | Gooseneck          |
| Temperature Rating    | 40 - 140 Degrees F |
| Type                  | Faucets            |
| Water Inlet Size      | 1/2 Inches         |

Notes & Details

Perfect for busy commercial kitchens, this Regency wall-mount faucet with 3 1/2" swivel gooseneck spout is an excellent choice when you need a reliable, affordable water fixture for your facility! Thanks to a 3 1/2" long and 8" tall swivel gooseneck spout, this faucet delivers water exactly where you need it. The design provides maximum flexibility for washing your hands or filling pots and pans, and it can be folded out of the way when not in use.

Water exits the faucet with a 1.2 GPM flow rate, which creates a soft flow pattern with minimal splashing. The faucet installs on your wall or sink backsplash on a pair of 4" centers and connects to the facility water lines with a set of 1/2" NPSM inlets. The faucet body is made from chrome-plated brass that complements nearly any design aesthetic, and the water flow is controlled by a pair of simple zinc handles. An installation kit is required for setup (sold separately).

 **WARNING:** This product can expose you to chemicals including Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).