




Regency NSF Chrome 5-Shelf Angled Stationary Merchandising Rack - 18" x 60" x 74"

#460EC1860SDS



Technical Data

Length	60 Inches
Width	18 Inches
Height	74 Inches
Angle Height	4 Inches
Post Diameter	1 Inch
Capacity	2200 lb.
Capacity (per Shelf)	400 - 600 lb.
Casters	Without Casters
Color	Silver
Features	NSF Certified

Features

- Includes (4) 18" x 60" slanted shelves, (1) 18" x 60" flat shelf, and (4) 74" tall stationary posts
- Attractive chrome design great for front-of-house display; built for dry environments
- 3-sided shelving frame included to ensure overall stability
- Shelves adjust along posts for convenient, custom shelving
- Each slanted shelf holds up to 400 lb. of weight; flat shelf holds up to 600 lb.

Certifications



Certified by NSF

Technical Data

Finish	Chrome
Material	Steel
Number of Shelves	5 Shelves
Style	Adjustable Stationary Vented
Type	Merchandising Racks Shelving Kits
Usage	Dry Environments Front of House Garage Kitchens Retail Stock Rooms Warehouse

Notes & Details

Outfit your retail business with this Regency chrome 5-shelf angled stationary merchandising rack! Featuring (4) 18" x 60" slanted shelves and (1) 18" x 60" flat shelf, the unit is perfect for use in your front-of-house area to display a wide range of products. The slanted shelves make for easy access and visibility, while the flat shelf provides merchandising versatility. Plus, each of the shelves is adjustable along the rack's (4) 74" tall posts to accommodate your ever-evolving product offering!

This particular merchandising rack is built with a chrome finish, making it attractive for display areas and suitable for dry environments. For added structural stability, the rack comes standard with a 3-sided frame that attaches to the posts. Its weight capacity is impressive too, with each slanted shelf accommodating up to 400 lb. of evenly distributed weight and the flat shelf holding up to 600 lb. of weight. This commercial-grade construction ensures that it's built to last, even with constant use in high-volume operations.