



Regency 24" x 48" Green Epoxy 3-Sided Frame for Wire Shelving

#460EG2448FRM



Technical Data

|                        |                           |
|------------------------|---------------------------|
| Length                 | 48 Inches                 |
| Width                  | 24 Inches                 |
| Compatible Shelf Width | 24 Inches                 |
| Color                  | Green                     |
| Component Type         | Shelving Frames           |
| Features               | NSF Certified             |
| Finish                 | Epoxy                     |
| Material               | Steel                     |
| Type                   | 3-Sided Frames Components |

Features

- Great for damp storage environments
- Reinforces your shelving unit
- 3-sided design attaches to four posts
- Includes 4 pairs of split sleeves
- Easy to assemble

Certifications



Certified by NSF

## Technical Data

|       |                                                                                    |
|-------|------------------------------------------------------------------------------------|
| Usage | All Environments<br>Dry Environments<br>Kitchens<br>Moist Environments<br>Walk-Ins |
|-------|------------------------------------------------------------------------------------|

## Notes & Details

This Regency 3-sided green epoxy frame for wire dunnage racks adds extra stability to your shelving unit. The 3-sided design attaches to all four posts of your shelving unit to make sure that your storage unit is strong and secure, no matter how much you need to store. The green epoxy finish is ideal for moist storage environments like cold storerooms, walk-in refrigeration units, and dish rooms since it is rust resistant.

This shelving frame is especially well suited for dunnage racks, as it adds support and helps fortify the racks to accommodate their heavy loads. It's also perfect for standard shelving units when a shelf is skipped. A skipped shelf diminishes the unit's rigidity by focusing weight onto the posts, which increases the chance of buckling. When the frame is added into the open space, it helps to more evenly distribute weight and to enhance structural rigidity.