

Super Automatic Espresso Machine Accessories

Model	Description
Purity C500 Water Filter Starter Kit (250-00011)	Included with purchase of super automatic espresso machines. Kit includes filter, water test kit, and filter head with variable bypass adjustable to local water conditions. Weight: 13 lbs. NSF Certification
Replacement Water Filter Cartridge (250-00012)	Replacement filter cartridge for Purity C500 water filter. Weight: 12 lbs.
Base Cabinet - Korinto (250-00015)	Base cabinet for use only with Korinto 1/2. Sides of cabinet are black, powder-coated metal, countertop is black Formica. Dimensions: 32.7" H x 16" (base), 26" (countertop) W x 20.5" D. Weight: 60 lbs.
Cup Warmer (250-00016)	Cup warmer with 2 shelves. Will hold 40 standard espresso cups or 24 standard cappuccino cups. 120V / 0.5 kW / 5A / 1 Ph Dimensions: 19.6" H x 13" W x 15" D. Weight: 33 lbs.
MiniFridge - Kobalto 2/2 FM (250-00017)	Small refrigerator for use only with Kobalto 2/2 FM, designed to be placed next to espresso machine, completely insulating and refrigerating up to a 1 gallon container of milk. Built-in hose hole. 120V / 0.1 kW / 1A / 1 Ph Dimensions: 13.5" H x 8 7/8" W x 18" D. Weight: 35 lbs.
Installation Package (80598)	Required for all super automatic espresso machines to qualify for factory warranty. The install, start, and adjust program includes limited installation, equipment inspection, equipment start-up, and operator training by a single person in locations 35 miles or less from a Grindmaster-Cecilware Certified Service Provider. When installation is purchased with a machine, the unit will be shipped to the installer. The customer must provide the following for installation: 1. Appropriate electric service within 4 feet of the machine's location for electric hook-up including appropriate heavy duty grounded receptacle with its own breaker. 2. Access to cold water with a minimum of 30 psi pressure with adequate shut-off valve within 6 feet of the machine's location on units requiring water line hook-up. 3. Adequate drain availability for flexible drain hose on units requiring water line hook-up. 4. Adequate and appropriate space to position unit. * Additional charges (i.e. removal of old equipment, work required to reach compliance with installation requirements above, travel time outside stated radius, or other expenses outside a normal installation situation) are the responsibility of the customer. Contact the factory for special Start and Adjust pricing for multiple units in one location.