

3320 Series Commercial Fan Forced Wall Heater

40



Features

- Disconnect switch
- Automatic fan delay circuit
- Automatic reset thermal limit
- Powder coated 18 gauge steel grill with extruded Aluminum front frame
- Steel block fin element
- Vane axial fan blade: 600 RPM motor; 175 CFM
- Rough-in dimensions: 14 1/8" Wide x 19 1/2" High x 4" Deep
- Grill dimensions: 15 29/32" Wide x 20 27/32" High
- Built-In tamper proof thermostat
- Made in U.S.A.

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



Product Specifications

Furnish and install Heavy-Duty Forced Air wall heaters, where specified. The heaters shall be constructed of a heavy 18 gauge steel housing with an extruded Aluminum frame. The rough-in dimensions are 14 1/8" Wide x 19 1/2" High x 4" Deep. The units shall be available in ratings from 750 to 4800 Watts at 240, 208, and 277 Volts. The heaters shall have a low-speed 600 RPM, 4-pole motor which drives a vane axial blower to deliver a quiet 175 CFM of down flow air. The heating element shall be of the sealed tubular type with large, parallel steel fins for quick heat transfer. Unit shall have as a standard, a thermal overload cut-off for added safety, fan delay switch and built-in tamper proof thermostat which shall be calibrated to provide a range of 0°F. to 110°F. and manual disconnect switch. Optional accessories shall include a surface and semi-recess mounting adapter. All heaters shall be listed by ETL. The heating element shall be supplied with a manufacturer's 1-year limited warranty.

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	BTUs	VOLTS	AMPS	WT. (LBS)	LIST
IN-BUILT SINGLE POLE TAMPERPROOF THERMOSTAT (0° - 110° TEMPERATURE RANGE) FOR DOUBLE POLE THERMOSTAT REPLACE "T" IN MODEL NUMBER WITH "T2" -- ADD \$50							
03820502	E3321TD-RP	750	2560	120	6.25	26	798
03819902	E3322TD-RP	1000	3413		8.3		
03808802	E3323TD-RP	1500	5120		12.5		
03809302	F3326TD-RP	4000	13800	208	19.2		813
03810202	F3327TD-RP	4800	16560		23		854
03809402	HF3323TD-RP	1500 / 1125	5120 / 3840	240 / 208	6.2 / 5.4	27	813
03809502	HF3324TD-RP	2000 / 1500	6284 / 5120		8.3 / 7.2		
03809602	HF3325TD-RP	3000 / 2250	10350 / 7763		12.5 /10.8	29	
03809702	HF3326TD-RP	4000 / 3000	13800 / 10350		16.7/14.4		
03810302	H3327TD-RP	4800	16560	240	20		845
03809802	G3323TD-RP	1500	5120	277	4.1	26	812
03809902	G3324TD-RP	2000	6284		7.2	27	
03810002	G3325TD-RP	3000	10350		10.8	29	
03810102	G3326TD-RP	4000	13800		14.4		
03810402	G3327TD-RP	4800	16560			17.3	
03980702	J3326TD-RP*	4000	13800	208	11.11	30	978
03980802	J3327TD-RP*	4800	16560		13.33		1027
03980902	K3326TD-RP*	4000	13800	240	9.64		978
03981002	K3327TD-RP*	4800	16560		11.57		1027
International Models							
03964202	M3324TD-RPi	3360/1680	11468/5734	220	15.3/7.64	27	813
03964302	M3325TD-RPi	4032/2016	13761/6881		18.3/9.16		

*Indicates 3-Phase model. All other models are 1-Phase.

Accessories

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	TYPE	WT. (LBS)	LIST
03778502	BOX 3310	Additional Rough-in Box	Field Installed	3	124
03784502	3320EX33	4" Surface Mounting Frame		1	116
03829302	3320EX16	2" semi recess extender		1	99
-----	Suffix - HD	16 Gauge Steel Heavy Duty Grill	Factory Installed	2	127