




Stainless Steel Braided Water Connectors For Dishwasher (EF-DC-Series)

Reliable braided water connectors for dishwasher installation. Easyflex flexible braided water connectors provide protection from vibration and bursting under extreme pressure surge. Various end connections make jobs easier and reinforced PVC hose braided with stainless steel are durable and all lead-free certified.

FEATURES

- Durable, flexible water connector with reinforced PVC inner hose, braided with stainless steel.
- Chrome plated brass hex nuts for corrosion resistance.
- Reliable nut-to-hose connection with sturdy pneumatic crimp.
- EPDM washer provides safe and reliable water tight sealing.

MATERIALS

Braided Jacket	Stainless Steel 304 (ASTM A240)
Inner Hose	Reinforced durable PVC
Fittings	Anti-corrosion Chrome-Plated Brass
Washer	EPDM
Ferrule	Zinc plated steel
Elbow	Brass

SPECIFICATIONS

Max. Working Temperature	180°F (82°C)
Max. Working Pressure	125psi (8.6 bar)

DESIGN CERTIFICATIONS AND APPROVALS

- cUPC/ NSF 61 Compliant for safe drinking water
- NSF 372 Compliant : Lead-Free
- ASME A 112.18.6-2009 / CSA B 125.6-2009



Job Name :

Engineer / Architect :

Job Location :

Wholesaler :

Submittal Date :

Contractor :



WEST OFFICE
(888) 577-8999
EAST OFFICE
(855) 388-2600

Easyflex reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modification on Easyflex products previously or subsequently sold.

Stainless Steel Braided Water Connectors

for Dishwasher (EF-DC-Series)

Image	Part #	Description		Qty / Box
		Hose & Fittings	Length	
	EF-DC-38C38L-48	DC SS Braided Dishwasher Connector 3/8" Compression x 3/8" Elbow	48"	50
	EF-DC-38C38L-60		60"	50
	EF-DC-38C38L-72		72"	50
	EF-DC-38C38L-96		96"	50
	EF-DC-12C38L-60	DC SS Braided Dishwasher Connector 3/8" Compression x 3/8" Compression	60"	50
	EF-DC-38CHBL-48	DC SS Braided Dishwasher Connector 3/8" Compression x 3/8" Compression	48"	50
	EF-DC-38CHBL-60		60"	50
	EF-DC-38CHBL-72		72"	50