


Waterloo 0.65 GPM Pre-Rinse Spray Valve


#750PRSVLF



Item #: 750PRSVLF Qty: _____

Project: _____

Approval: _____ Date: _____



Features

- 0.65 GPM flow rate
- Heavy-duty construction
- Fits all Waterloo pre-rinse units
- Ergonomic squeeze handle with hold-down ring
- Features a 7/8"-20 UNEF inlet

Certifications



CSA, US and Canada




Certified by NSF

Technical Data

Features	ASME A112.18.1-2018 / CSA B125.1-18 NSF Certified
Flow Rate	0.65 GPM
Inlet	7/8"-20 UNEF Male Inlet
Type	Spray Valves

Plan View

750PRSV



Notes & Details

This Waterloo 0.65 GPM pre-rinse spray valve is an excellent choice when you need to replace a broken valve or upgrade an old one! Designed to provide the industry-leading quality you expect, this spray valve has a heavy-duty body with metal construction to prevent leaks and keep up with even fast-paced dishrooms. It boasts a 0.65 GPM low flow rate to blast away heavy soil deposits and ensure that glassware and dinnerware come out of the dishwasher clean and ready to use. It comes with a hold-down ring so that you can lock the valve into the on position for constant use, and it has a 7/8"-20 UNEF inlet.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.